

ALL **on** LINE C  
**on** DEMAND **on** CA



TOWABLE GENERATORS

**KOHLER**<sup>®</sup>

## TAKING POWER TO NEW PLACES

With a breadth of nine products ranging from 20 kW all the way up to 500 kW, KOHLER® is your single source for all your towable generator needs. With features like heavy-duty camlock kits, rugged trailer and housing construction to withstand the elements, and state-of-the-art digital controllers, KOHLER is quickly becoming the clear choice in the industry. Unlike a standby generator, towable generators adapt to your needs, wherever they may be. And you can take extra comfort in Kohler's 85 years in the generator business and our unmatched network of generator-specific service points. Bring it on with KOHLER towable generators.

- 20 kW
- 40 kW
- 60 kW
- 100 kW
- 125 kW
- 150 kW
- 200 kW
- 275 kW
- 500 kW

## AN ALTOGETHER DIFFERENT LEVEL OF SERVICE

Anybody can claim to offer an unrivaled level of support, but it is another thing to deliver on that promise. Kohler requires all of its certified distributors and dealers to be available 24 hours a day, seven days a week. No exceptions. And for a distributor/dealer to be registered as a KOHLER service point, a rigorous training program must first be completed, as well as routinely updated.

Unlike other generator manufacturers, Kohler-certified service sites, available across a complete coverage area, specialize in power. This means our service network can be called on for anything related to your towable generator and its components. Because an exceptional generator deserves an exceptional service plan.

## KOHLER® TOWABLE GENERATOR CONTROLS

KOHLER DECISION MAKER® controllers come standard on all of our towable generators for efficient operation.

- Incredibly user-friendly
- Simple, reliable controls
- Operates in manual or automatic mode



KOHLER Decision-Maker® 1000 is standard on 20-275 kW models.

KOHLER Decision-Maker® 4000 is standard on 500 kW model.



KOHLER 100REOZT Towable Generator

## TOWABLE GENERATOR OPTIONS

- Camlock options (up to 100 kW), quick-on/quick-off attachment to the power source
- Battery charger for quick deployment

## STANDARD FEATURES



**KOHLER® DECISION-MAKER®** controls with viewing window



**Busbar connection with locking access and strain relief for enhanced safety and load connection (above 200 kW)**



**Battery Disconnect Switch** ensures your battery will maintain its charge even after periods of prolonged storage



**Oil Drain Pump** for simplified maintenance



**Voltage Selector Switch** simple to configure single- and three-phase voltage selector switch (up to 200 kW)



**Convenience sockets** provide power directly from the generator

- All KOHLER towable generators are emission-compliant
- Rugged, heavy-duty DOT-approved trailer
- Reconnectable bus (above 200 kW) with locking access and strain relief for enhanced safety
- Distribution panel features multiple sockets with individual circuit breakers per receptacle
- Double-wall fuel tank provides 110 percent containment of oil, coolant and fuel
- Sound enclosures keep noise levels down to 64 dBA on small units and 75 dBA on large units
- Easy maintenance access – large lockable doors with window to view controls
- Two-stage air filter
- Single point lift

MODEL SPECIFICATIONS	20REOZT	40REOZT	60REOZT	100REOZT	125REOZT	150REOZT	200REOZT	275REOZT	500REOZT	
Standby Rating @ 480V (kW/kVA)	23/29	40/50	65/81	106/133	127/159	154/192	213/266	280/350	504/630	
Prime Rating @ 480V (kW/kVA)	21/26	36/45	59/74	96/120	116/145	140/175	194/242	255/318	458/573	
Voltage - 1 Phase	110/127/139/240/254/277 - Switchable							n/a		
Voltage - 3 Phase	208/220/240/415/440/480 - Switchable							208/220/240/415/440/480 - Reconnectable		
Main Circuit Breaker (Amps)	80	160	250	400	400	630	630	800	1600	
"Sound Level Full Load dBA @ 23 feet"	65	68	69	68	71	69		71	76	
EPA Emission Tier	4i		3					2		
Fuel Tank Capacity (Gal)	61		133		229			251	468	
FUEL CONSUMPTION										
Full Load (Hours)	32	19	29	16	23	21	16	14	14	
75% Load (Hours)	43	26	37	18	27	23	26	18	20	
50% Load (Hours)	56	38	53	25	36	31		27	29	
STANDARD FEATURES										
Control	KOHLER® DECISION MAKER™ 1000								DEC 4000	
Voltage Selector Switch	standard						n/a			
Reconnectable Voltage	n/a						standard			
110% Fluid Containment	standard									
Battery disconnect switch	standard									
Water/ Fuel Separator	standard									
Trailer	single axel			tandem axel						

For more information on KOHLER TOWABLE GENERATORS, call **800-544-2444** or visit **KohlerPower.com/Industrial**



**KOHLER**®

Call toll-free in the U.S. and Canada  
**800.544.2444** or visit **KohlerPower.com/industrial**

KOHLER POWER  
KOHLER, WISCONSIN 53044

Printed in U.S.A  
G12-337 6/09  
©2009 by Kohler Co.

P. 920.565.3381  
F. 920.459.1646

Use of this material for reproduction on the Internet and World Wide Web is strictly prohibited without written permission from Kohler Co. KOHLER, ON™ and the color green are trademarks of Kohler Co.